



# MAXPAR® G2 60

GROUP II BASE OIL

Analysis	Test Method	Typical Values	Standard CoA
Appearance	Visual	Clear & Bright	–
Color	ASTM D1500	L0.5	✓
Viscosity, SUS @ 100°F	ASTM D2161	64	✓
Viscosity, cSt @ 40°C	ASTM D0445	9.5	✓
Viscosity, cSt @ 100°C	ASTM D0445	2.5	–
Specific Gravity, 60/60°F	ASTM D4052	0.867	✓
Density, lb/gal @ 60°F	–	7.23	✓
Gravity, API	ASTM D4052	31.7	✓
Flash Point (COC), °F (°C)	ASTM D92	345 (173)	✓
Pour Point, °F (°C)	ASTM D97	-34 (-36)	✓
Aniline Point, °F (°C)	ASTM D0611	215 (101)	–
Sulfur, ppm	ASTM D5453	< 20	–
Water, ppm	ASTM D6304	30	–
Aromatics, vol%	UV Correlation	2.0	–

CAS No. 64742-55-8 : Hydrotreated petroleum distillate, light paraffinic

**RESOLUTE OIL**

1-866-690-0417 | 102 Magellan Circle STE B, Webster, TX 77598 | [hello@resoluteoil.com](mailto:hello@resoluteoil.com)

Product Bulletin / Revision 2019-09-20