

RODENT PROOFING COMPOUND - PROFESSIONAL USE

RODENTSTOP™

-  PHYSICAL BARRIER
- +
-  INSTANTLY WATERPROOF
- +
-  NO PESTICIDE
- +
-  INSTANTLY EFFECTIVE
- +
-  IPM COMPLIANT
- +
-  PAINTABLE WHEN SET
- +
-  METAL FIBERS REINFORCED
- +
-  METAL DETECTABLE

From the makers of:



KEEP OUT OF THE REACH OF CHILDREN.
Not for internal consumption.

PREMIUM RODENT BLOCKER

RodentStop is an animal friendly barrier pest control paste, reinforced with metal fibers for outstanding protection. Acts as a physical barrier, sealing seams, cracks and holes to prevent ingress from rodents and other pests. RodentStop contains no pesticides, is instantly waterproof and highly effective. All this makes RodentStop fully compliant with the Integrated Pest Management (IPM) approach.

APPLICATIONS

Gnawed openings, cracks, joints and holes in brickwork, brick walls, sidings, settlement cracks, steel, cast iron, PVC, drains, sewage pipes and electrical ducts.

HOW TO USE

Use only as directed. Ensure surface is clean and dry. Openings should be at least ¼ inch [6 mm] wide for RodentStop to achieve proper adhesion. Connect the RodentStop cartridge to a caulking gun and cut the nozzle of the cartridge with pliers, scissors or a sharp knife to your desired bead size. Apply RodentStop to the area that needs to be sealed, with a depth of at least ¾ inch [18 mm]. Make sure the area is completely filled to the edges on all sides. To finish, smooth the RodentStop putty with a small trowel. The required layer depth may vary in order to achieve maximum blocking capacity. RodentStop can be installed in cold or warm weather conditions (-50°F / 170°F) [-45°C / 75°C]. The surface will be dry after 48 hours in normal weather conditions (70°F / 21°C), at which point it can be painted if so desired. Wear gloves for convenience. Wash hands after use. Clean tools with a dry cloth after use. If necessary, use mineral spirits on tools for cleaning. Do not apply near heat sources.

IMPORTANT NOTICE & WARRANTY

To the extent consistent with applicable law, the manufacturer warrants that this product will be free from defects in material and manufacturing for 90 days from the date of purchase from an authorized distributor. As such, the product is reasonably fit when used in accordance with the directions for use.

This warranty does not extend to the use of RodentStop in a manner inconsistent with its labeling or when used under abnormal conditions. Many factors beyond the control of the manufacturer and/or uniquely within the user's knowledge and control can affect the use and performance of RodentStop in a particular application. Given the variety of factors that can affect the use and performance of RodentStop, the user is solely responsible for evaluating RodentStop and determining whether it is fit for a particular purpose and suitable for the user's method of application. All such risks shall be assumed by the user.

PRECAUTIONARY STATEMENTS

RodentStop is not considered to be hazardous under the OSHA HazCom 2012 regulations or the Federal Hazardous Substances Act, for consumer products.

Storage: Store product in original container
Color: Grey
Weight: +/- 12 oz. / +/- 340 g.

Manufactured for PelGar International Ltd.



PelGar USA
215 Evergreen Ct.
Saylorsburg, PA 18353
www.pelgar-usa.com

PelGar Asia Pacific
Level 22, 69 Ann St.
Brisbane, QLD 4000
www.pelgar.asia

International

RodentStop™ is a trademark of PelGar International Ltd.

